

# Alarm Control

System TCP/IP 2G/4G

## FC-7640 PRO

- 8 tamper-checking wired zone, 32 wireless zone, 88 BUS zone.
- 8 programmable access wireless remote.
- 8 programmable access keypad, 32 wireless appliance switch, 8 wireless siren.
- Can extend GPRS wireless communication module, support GPRS data transmission.
- Can extend programmable Relay module, serial module.
- Can set 8 private telephone numbers. ☑ Remote voice prompt operation.



TCP/IP 2G/4G Free APP Control With Wifi IPCam Monitoring Control

# Specification

General	
System NetworkT	TCP/IP+2G/4G Dual NetworkT
Alarm Zones	32 Wireless+8 Wired + 56 RS485 + 32 Power Bus
Dimensions	290x240x87 mm (WXHxD)
Housing Material	ABS Fire-resistant Box
Wireless Frequency	433MHz/868MHz
Installation Location	Indoor Use For Wall Mounted
Menu Voice Guidance	Customized
DHCP Function	Support
Duress Password	Yes
Entry & Exit Delay	Yes
Number of Users	32 Users + 1 Admin +1 Main
Number of voice phone No.	4
Number of wireless remotes	8
Number of wired keypad	8
Number of wireless doorbell	1
Number of wireless Switch	32Ch
Partitions And Areas	4
Event log	512
Wireless Siren	4 for dual way siren, multiple for single way siren
PGM Outputst	4
Event log	1000
Backup Battery Type	12V DC, 7ah lead acid battery
Max. run time on backup Battery	16 h if connect 1 wired keypad
Max. receiving range (outdoors)	100 m
Max. sending range (Outdoors)	150 m

Power Supply Unit	15V/3A
GSM Dialing Protocols	Ademco Contact ID
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, Meian CMS
CMS Platform Docking Way	Support 2 CMS Server Address Main Server +Backup Server (Meian Server/SIA-TCP,SIA-UDP)
Camera Supported	Support
WEBIE	Support
Packing	4 Sets/Carton
Certifications	CE,FCC,ROHS