

Bullet

IP Camera 4/5mp WDR

BI



Human detection IP camera, adopt Ingenic 22nm chip, built-in AI algorithm, H.265 / H.264 Compression format, D-WDR, 3D DNR, 3.6/4mm lens is optional, 2 pcs IR lights, IR distance 20M

Features

- 4MP and 5MP is option, fixed lens
- 2 pcs IR light, IR distance is 20M
- Built-in human detection algorithm;
- Detection frame 5fps, detect 5 people at the same time;
- Low consumption, low code stream, low delay;
- H.265 compression format, save bandwidth and storage space;
- Support smart IR to avoid Infrared over-exposure at night;
- Support ICR auto switch, achieve best result for D&N video;
- PoE, two-way audio intercom is optional;
- Support 3D DNR and digital WDR;
- Support auto-electronic shuttle to suit different surveillance environment
- Support HTTPS encrypted transmission
- Support Onvif, email, NTP service
- Change the password during initial use to ensure the security of the password

Specification

Camera			
Model	EH-HN-BI-2M--G3	EH-HN-BI-3Q-G4	EH-HX-BI-5B-G4
Chip	T31N	T31N	T31X
Sensor	GC4063	SC3335	GC4653
Lens	3.6MM	4MM	4MM
D&N	ICR Switch, Auto/Color/B&W/CDS Trigger		
D-WDR	D-WDR (off/low/middle/high)		
IR Led	6 pcs IR leds, IR distance 25M		
3D DNR	Off/Low/Middle/High/Higher		
Defog	Off/Low/Middle/High		
Mirror	Off/ Horizontal Mirror/Vertical Mirror/180-degree flip		
Image Setting	Brightness, Contrast, Sharpness, Saturation, Chroma		
Human Detection			
Detection Quantity	≤5 people human		

Human Size	Human Pixel ≥ 40*40
Detection Ratio	≥99% (meet above requirement)
Capture Corresponding Speed	≤1s
Max Detection Frame	5fps/s
Fault Detection Ratio	≤2%
Detection Part	People with any posture including half body, head, hand, shoulder
Track People	Support
Detection Mode	Support static and dynamic human detection
Detection Method	Image detection during day time or night time with lights or IR LEDs
Detection Area	Appointed area, default full-screen
Upload Method	Upload it under private protocol
Trigger Method	Video trigger

Audio & Video Encoding

Video Encode Standard	H.265/H.264		
Chip	Main stream: 4MP@20fps, 3MP@20fps 2MP@25fps 720P@20fps Sub-stream: D1(720*576), VGA (640*360)	Main stream: 4MP@20fps, 3MP@25fps 1080P@25fps Sub-stream: D1(720*576), VGA (640*360)	Main stream: 5MP@20fps, 4MP@25fps 3MP@25fps 1080P@25fps Sub-stream: D1(720*576), VGA (640*360)
Video Code Rate	Fixed code rate, variable code rate (Main stream: 160Kbps-4000kbps)		
Video Type	Composited stream/video stream		
Audio Standard	G.711u / 64Kbps		
Network Function			
Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, NTP, PPPOE, UPNP, SMTP		
Connection Protocol	ONVIF, GB28181 (Option)		
Security Mode	Authorized user name and password, HTTPS encryption, AES connecting encryption, RTSP verification		

Motion Detection Set detection area, can set multi-level sensitivity

Shield Alarm Support 1 area

Privacy Mask Support 4 areas

Schedule Linkage Snapshot, email

Device Abnormal Inspection Support network broken alarm, IP conflict alarm, illegal visiting alarm

Character Overlay (OSD) Title, time and date overlay, multi-line, and color of characters optional

Port

Network Port RJ45 10M/100M network self-adaptation

Audio NA

General

Power Supply DC12V /PoE (option)

Working Temperature -20°C ~ 55°C

Working Humidity 0%~90%

Dimension

