

Alarm System

WiFi/2G/4G Smart Home

HA-IIIIGW



ST-IIIIGW Smart Home WiFi , Smart Home Automation, Smart Control Home

Specification

Overview

| | |
|---|---|
| Dimensions | 253x194x35mm (LxWxH) |
| Housing Materials | ABS Plastic + Touch Keyboard Tempered Glass Surface |
| LCD Display | 2.8 inch TFT Image Large Digital Display Screen Date/Temperature/Arm/Disarm/Home Stay/Zone/CMS/App/AC Status/Battery Status Indication. |
| Menu Voice Guidance | EN/IT/FR/ES/RU More |
| Kit Weight | 1.2Kgs |
| Kit Included | 1 x Wireless Indoor PIR Motion Detector MC-565DMT 1 x Wireless Door Magnetic Sensor MD-211R 2 x Wireless Remote Controller PB-443R 1 x Power Supply 2 x CR123A Lithium Batteries (Longlife Time 3 Years) 2 x RFID Card Readers |
| System Network | Wifi+GSM/Gprs |
| Numbers of Users | 16 |
| Number of Wired Zones | 8 |
| Number of Wireless Remote or Wireless Keypads Control | 8 |
| Number of Wired Keypads | 0 |
| Number of Wireless Zones | 32 |
| Number of Users Voice Phones | 4 |
| Number of Wireless Doorbell | 1 |
| Number of Smart Switch | 16ch |
| Number of RFID Tags | 16 |
| Number of Wireless Siren | 1 x Dual Way Siren No limited For Single Way Siren |
| Associated Zones | 8 Groups |
| Timing Arm/Disarm | 4 Groups |
| Number of RFID Tags | 16 |
| PGM Port Output | 1 PGM Port for Program |
| Mobile App | Free Mobile Android and IOS Application support. |

| | |
|------------------------|--|
| GSM Antenna | Internal GSM Antenna |
| Event Logs Query | 512 |
| RF Radio Frequency | 433mhz or 868mhz for optional |
| Integrated Siren | 85dB at 1M |
| Backup Battery | 3.7V/1A Rechargeable Lithium Battery |
| Max Receiving Range | 150M |
| Power Supply Unit | 15V/2A |
| Protocols | Ademco Contact ID |
| Tamper | YES |
| Mobile Client | Smart Security (IOS/Android) |
| WEB GUI | YES |
| CMS | Support 2 CMS Server Address, Main Server + Backup Server (Meian Server/SIA-TCP,-SIA-UDP) |
| Camera Support | Unlimited for the Quantity |
| Low Battery Indication | Detector sends the status report to host panel every 1 to 3 hours, the corresponding Zone No. And voltage symbol will be display on the LCD screen and also report to the CMS |
| Duress Password | The host can make the illusion of disarming when the users is threatened by the intruder and actually still send an alarm message to notify the alarm receiver. |
| Zone Type Programmable | Users can program all preset zone types according to needs. Support delay zone, perimeter zone, internal zone, SOS, 24H, Fire alarm. |
| WIFI Cameras | Users can access to MEIAN WiFi cameras at unlimited quantities from App (Smart Security), each cameras can link to one of the wireless and wired zone devices to alarm. Once triggered, users can browse the alarm video and alarm data from the App and alarm center. |
| Zone Name Programmable | User can learn the device and edit the zone name by manual from App. If devices be triggeres. It will report thr alarm data (Zone No. And Zone Name) indication on the LCD display. Also CMS, SMS and APP. |
| All Around Safeguard | System with all around safeguard notifications. Door open/closed, devices low battery notification, AC On/Off, Tamper Alarm, Vandal Alarm, Duress Alarm, Fire Smoke and Gas Leakage, Water Leakage, Vibration Detector, Glass Break Alarm, Curtain Intruder Alarm, CCTV and camera monitoring Alarm. |