

LCD Display WIFI GPRS Intruder Alarm Security System

HA-VII



HA-IIGW is a DIY, self monitoring home security system, with Wifi and GSM network.2.8" TFT color display, with voice list text menu for all operations. Adding wireless devices and WiFi cameras via the app as soon as you connect to your Router, free cloud services all over the world. Users remote control via SMS, App and CMS client, which are all around to give home more protection. Commonly used in the residences, apartments, shops, office and commercial premises.





Specification

Overview	
Housing Materials	ABS Plastic+Touch Keyboard Tempera- ed Glass Surface
Installation	Indoor Wall Mounted Table Set
LCD Display	2.8 inch TFT Image Large Digital Display Screen Date/Temperature /Arm/Disarm/Home Stay/Zone/CMS/ App/AC Status/Battery Status Indica- tion
Menu Voice Guidance	EN/IT/FR/ES/RU More
Kit Weight	1.20KGs
Menu Voice Guidance	EN/IT/FR/ES/RU More
Kit Included	1 x Wireless Indoor PIR Motion Detector MC-565RDMT 1 x Wireless Door Magenetic Sensor MD-211R 2 x Wireless Remote Controller PB-443R 1 x Power Supply 2 x CR123A Lithium Batteries (Long life time 3 Years) 2 x RFID Card Readers
System Network	1.HA-VII 4G+WIFI network 2.HA-VII 4G+IP network
Number Of Users	16
Nuser Of Wired Zones	8
Number Of Bus Zones	0
Number Of Wireless Remotes Or Wireless Keypads Control	8
Number Of Wired Keypads	0
Number Of Wireless Zones	32
Number Of User Voice Phones	4
Number Of Wireless Doorbell	1
Number Of Smart Switch	16CH
Number Of RFID Tags	16
Number Of Wireless Siren	1* Dual Way Siren No limited For Single Way Siren

Associated Zones	8 Groups	
Timing Arm/Disarm	4 Groups	
PGM Port Output	1 PGM Port for program	
GSM Antenna	Internal GSM Antenna	
Event Logs Query	512	
RF Radio Frequency	433mhz or 868mhz for optional	
Backup Battery	3.7V/1A Rechargeable Lithium Battery	,
Integrated Siren	85dB @ 1M	
Backup Battery	3.7V/1A Rechargeable Lithium Battery	,
Max Receiving Range	150M	
Max Receiving Range Max Sending Range	150M	
Max Sending Range	150M	
Max Sending Range Power Supply Unit	150M 15V/2A	
Max Sending Range Power Supply Unit Protocols	150M 15V/2A Ademco Contact ID	
Max Sending Range Power Supply Unit Protocols Tamper	150M 15V/2A Ademco Contact ID YES	
Max Sending Range Power Supply Unit Protocols Tamper Mobile Client	150M 15V/2A Ademco Contact ID YES Smart Security(IOS/Andriod)	

