

## **Home Alarm**

Intrusion Security System

## **HVA-VGT**

- Home Monitor HD Pro Camera (Support 8 PCS With Meian Cameras)
- · With TCP/IP RJ45 Ethernet Port, Stable And More reliable.
- · With Wireless PIR Motion Detector, Door Magnetic Sensor, Remote Controller.
- · All the Wireless Device With Lithium Battery.
- No Need to Change Battery frequenly. It can keep using for 3-5 Years.
- · With pet immunity, door open/closed notification, Low battery indication,
- Alarm video linkage functions.
- · Intercom for talking, timing arm/disarm.



4G Smart home alarm, LAN IP, GPRS network, SIA + Wi-Fi camera with iOS/Android app push notifications. 2.8 inch TFT Color Display & Glass Touch Panel, TCP/IP 2G/4G With IP camera Home Security Alarm System





## **Specification**

RF Radio Frequency ASK 433/868mhz  Dimensions 280x205x74mm (wxhxd)  Housing Material ABS Cover+Tempered Glass  LCD Size 2.8" LCD display  System Network TCP/IP+GSM/GPRS (4G)  DHCP Function Support  Admin Password 1  User Password 16  Voice Phone No. 2  Number Wired 8  Remote and Keypads 8  Number of RFID 16  Support 16  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery  Max. receiving range (Outdoors)  Max. receiving range (Outdoors)  (Outdoors)  150m	ı	
Dimensions 280x205x74mm (wxhxd) Housing Material ABS Cover+Tempered Glass  LCD Size 2.8" LCD display  System Network TCP/IP+GSM/GPRS (4G)  DHCP Function Support  Admin Password 1  User Password 16  Voice Phone No. 4  CMS Phone No. 2  Number Wired 20nes 8  Remote and Reypads 8  Number of RFID 16  Lags (125KHz) 16  Number of wireless 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 150ms  Max. sending range 150ms  Max. sending range 150ms	General	
Housing Material ABS Cover+Tempered Glass  LCD Size 2.8" LCD display  System Network TCP/IP+GSM/GPRS (4G)  DHCP Function Support  Admin Password 1  User Password 16  Voice Phone No. 4  CMS Phone No. 2  Number Wired Zones 8  Remote and Keypads 16  Number of RFID 16  Number of wireless 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 100 m  Max. sending range 150 m	RF Radio Frequency	ASK 433/868mhz
System Network TCP/IP+GSM/GPRS (4G)  DHCP Function Support  Admin Password 1 User Password 16 Voice Phone No. 4 CMS Phone No. 2 Number Wired Zones Remote and Keypads Number of RFID tags (125KHz) 16 Number of wireless Zones  Zones  Nireless doorbell 1 Wireless Switch 16Ch Programmable Wired Output 1 Event log 512 Wireless Siren Support  Anti-tamper Alarm Support  Anti-tamper Alarm Programmable Wired Output 1 CSM Antenna: External Integrated Siren Yes (85dB @ 1m)  Backup Battery Max. run time on backup Battery Max. receiving range (outdoors) Max. sending range Max. sending range  Max. sending range  Integrated Siren  Max. sending range Integrated Siren  Max. receiving range Integrated Siren  Max. sending range Integrated Siren  Max. sending range Integrated Siren  Max. sending range Integrated Siren  Integrated Siren Integrated S	Dimensions	280x205x74mm (wxhxd)
System Network  TCP/IP+GSM/GPRS (4G)  DHCP Function  Support  Admin Password  1  User Password  16  Voice Phone No.  4  CMS Phone No.  2  Number Wired Zones  Remote and Keypads  Number of RFID 16  Tags (125KHz)  Number of wireless 32  Wireless doorbell  1  Wireless Switch  16Ch  Programmable Wired Output  Event log  512  Wireless Siren  Support  Anti-tamper Alarm  Support  Programmable Wired Output  1  GSM Antenna:  External  Integrated Siren  Yes (85dB @ Im)  Backup Battery  7.4V/IA  Max. run time on backup Battery  Max. sending range  (outdoors)  Max. sending range  1500  11  CSM Antenna:  1500  1	Housing Material	ABS Cover+Tempered Glass
DHCP Function Support  Admin Password 1  User Password 16  Voice Phone No. 4  CMS Phone No. 2  Number Wired 8  Remote and Keypads 8  Number of RFID tags (125KHz) 16  Number of wireless Zones 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  CSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 150m  Max. sending range 150m  Max. sending range 150m  Max. sending range 150m  Max. sending range 150m	LCD Size	2.8" LCD display
Admin Password 1 User Password 16 Voice Phone No. 4 CMS Phone No. 2 Number Wired Zones 8 Remote and Keypads 8 Number of RFID 16 Tags (125KHz) 16 Wireless doorbell 1 Wireless Switch 16Ch Programmable Wired Output 1 Event log 512 Wireless Siren Support Anti-tamper Alarm Support Programmable Wired Output 1 CSM Antenna: External Integrated Siren Yes (85dB @ 1m) Backup Battery 7.4V/IA Max. run time on backup Battery 150m Max. sending range 150m Max. sending range 150m Max. sending range 150m	System Network	TCP/IP+GSM/GPRS (4G)
User Password 16  Voice Phone No. 4  CMS Phone No. 2  Number Wired Zones 8  Remote and Keypads 16  Number of RFID tags (125KHz) 16  Number of wireless Zones 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 150m  Max. sending range 150m  Max. sending range 150m  Max. sending range 150m	DHCP Function	Support
Voice Phone No. 4  CMS Phone No. 2  Number Wired Zones 8  Remote and Keypads 8  Number of RFID 16  Number of wireless 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  CSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 150m  Max. receiving range (outdoors)  Max. sending range 150m  Max. sending range 150m	Admin Password	1
CMS Phone No. 2  Number Wired Zones 8  Remote and Keypads 8  Number of RFID 16  tags (125KHz) 16  Number of wireless 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  CSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 150m  Max. sending range 150m  Max. sending range 150m  Max. sending range 150m	User Password	16
Number Wired Zones 8  Remote and Keypads 8  Number of RFID 16  Number of wireless 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 100 m  Max. sending range 150m  Max. sending range 150m	Voice Phone No.	4
Zones 8  Remote and Keypads 8  Number of RFID 16  Number of wireless 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 100 m  Max. sending range 150m  Max. sending range 150m	CMS Phone No.	2
Keypads8Number of RFID tags (125KHz)16Number of wireless Zones32Wireless doorbell1Wireless Switch16ChProgrammable Wired Output1Event log512Wireless SirenSupportAnti-tamper AlarmSupportProgrammable Wired Output1GSM Antenna:ExternalIntegrated SirenYes (85dB @ 1m)Backup Battery7.4V/IAMax. run time on backup Battery6 hMax. receiving range (outdoors)100 mMax. sending range150 m		8
tags (125KHz)  Number of wireless Zones  32  Wireless doorbell  1  Wireless Switch  16Ch  Programmable Wired Output  Event log  512  Wireless Siren  Support  Anti-tamper Alarm  Support  Programmable Wired Output  1  CSM Antenna:  External  Integrated Siren  Yes (85dB @ 1m)  Backup Battery  7.4V/IA  Max. run time on backup Battery  Max. receiving range (outdoors)  Max. sending range  150m  1		8
Zones 32  Wireless doorbell 1  Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  CSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/IA  Max. run time on backup Battery 100 m  Max. receiving range (outdoors) 150 m  Max. sending range 150 m		16
Wireless Switch 16Ch  Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/1A  Max. run time on backup Battery 6 h  Max. receiving range (outdoors) 150 m  Max. sending range 150 m		32
Programmable Wired Output 1  Event log 512  Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/1A  Max. run time on backup Battery 100 m  Max. receiving range (outdoors) 150 m  Max. sending range 150 m	Wireless doorbell	1
Wired Output  Event log  512  Wireless Siren  Support  Anti-tamper Alarm  Support  Programmable Wired Output  1  GSM Antenna:  External  Integrated Siren  Yes (85dB @ 1m)  Backup Battery  7.4V/1A  Max. run time on backup Battery  Max. receiving range (outdoors)  Max. sending range  150m	Wireless Switch	16Ch
Wireless Siren Support  Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/1A  Max. run time on backup Battery 6 h  Max. receiving range (outdoors) 150 m  Max. sending range 150 m		1
Anti-tamper Alarm Support  Programmable Wired Output 1  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/1A  Max. run time on backup Battery 6 h  Max. receiving range (outdoors) 150m  Max. sending range 150m	Event log	512
Programmable Wired Output  GSM Antenna: External  Integrated Siren  Yes (85dB @ 1m)  Backup Battery  7.4V/1A  Max. run time on backup Battery  Max. receiving range (outdoors)  Max. sending range	Wireless Siren	Support
Wired Output  GSM Antenna: External  Integrated Siren Yes (85dB @ 1m)  Backup Battery 7.4V/1A  Max. run time on backup Battery 6 h  Max. receiving range (outdoors) 150m  Max. sending range 150m	Anti-tamper Alarm	Support
Integrated Siren  Yes (85dB @ 1m)  Backup Battery  7.4V/1A  Max. run time on backup Battery  Max. receiving range (outdoors)  Max. sending range		1
Backup Battery 7.4V/1A  Max. run time on backup Battery 6 h  Max. receiving range (outdoors) 100 m  Max. sending range 150m	GSM Antenna:	External
Max. run time on backup Battery  Max. receiving range (outdoors)  Max. sending range	Integrated Siren	Yes (85dB @ 1m)
backup Battery  Max. receiving range (outdoors)  Max. sending range	Backup Battery	7.4V/1A
(outdoors) 100 m		6 h
		100 m
,	Max. sending range (Outdoors)	150m

Power Supply Unit	12V/1.5A
GSM Band Frequency	850/900/1800/1900mhz
GSM Dialing Protocols	Ademco Contact ID
Firmware Upgrade Way	Web GUI/SD Slot
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, CMS Client
Mobile Client APP	Support
GSM Dialing Protocols	Ademco Contact ID
Firmware Upgrade Way	Web GUI/SD Slot
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, CMS Client
Mobile Client APP	Support
Camera Supported	Support
Packing	10 Sets/17.5kg/Carton
Certifications	CE,FCC,ROHS

