

Smart Socket

Wireless

smart socket is easy to control and with socket conversion as a whole. with intelligent remote control functions. it is a smart and secure products. smart socket can be plugged directly into other sockets or plug into the power strip. there are two USB ports and power socket accessible. smart socket for any types of socket to be converted places, such as hotel, office, home. etc.



PL-300R



PL-508



HA-4502

Specification

Overview		Overview		Overview	
Working voltage	DC 12V	WorkInput Voltage	100v-240vAC	Input voltageT	125V
Working current	<200mA@max	Working frequency	50~60Hz	Input frequency	50Hz/60Hz
Relay output power	0A/14VDC 10A/125VAC	Radio frequency	433MHz	Max.load current	10A
Debug Mode	ASK/FSK for options	RF Transmitting distance	100 meter indoor	Max.Power	2200W
Working Frequency	433mhz	Voltage Range	110Vac-230Vac/50H Z-60HZ	WIFI standard	WIFI 802.11 b/g/n
Wireless distance	(L*W*H) 70*70*25mm	Operate Temperature	-10°C ~ 55°C	WIFI frequency	2.4GHz
Installation	wall inside, wall mounting	Socket output power	3kw	Receive Sensitivity	98dBm
				PA output	19.5dBm
				Total consumption	TBD
				Indicator light	Blue LED
				Reference	FCC/CE/RHOS