XTEND INDONESIA
GLOBAL LEADING AI TECH COMPANY

www.xtendindonesia.co.id

Alarm System

WiFi/2G/4G Smart Home

HA-IIIGW

ST-IIIGW Smart Home WiFi , Smart Home Automation, Smart Control Home

Specification

Overview	
Dimensions	253x194x35mm (LxWxH)
Housing Materials	ABS Plastic + Touch Keyboard Tempered Glass Surface
LCD Display	2.8 inch TFT Image Large Digital Display Screen Date/Tempera-ture/Arm/Disarm/Home Stay/Zone/ CMS/App/AC Status/Battery Status Indication.
Menu Voice Guidance	EN/IT/FR/ES/RU More
Kit Weight	1.2Kgs
Kit Included	1 x Wireless Indoor PIR Motion Detector MC-565DMT 1 x Wireless Door Magnetic Sensor MD-211R 2 x Wireless Remote Controller PB-443R 1 x Power Supply 2 x CR123A Lithium Batteries (Longlife Time 3 Years) 2 x RFID Card Readers
System Network	Wifi+GSM/Gprs
Numbers of Users	16
Number of Wired Zones	8
Number of Wireless Remote or Wireless Keypads Control	8
Number of Wired Keypads	0
Number of Wireless Zones	32
Number of Users Voice Phones	4
Number of Wireless Doorbell	1
Number of Smart Switch	16ch
Number of RFID Tags	16
Number of Wireless Siren	1 x Dual Way Siren No limited For Single Way Siren
Associated Zones	8 Groups
Timing Arm/Disarm	4 Groups
Number of RFID Tags	16
PGM Port Output	1 PGM Port for Program
Mobile App	Free Mobile Android and IOS Applica-tion support.
GSM Antenna	Internal GSM Antenna
Event Logs Query	512
RF Radio Frequency	433mhz or 868mhz for optional
Integrated Siren	85dB at 1M
Backup Battery	3.7V/1A Rechargeable Lithium Battery
Max Receiving Range	150M
Power Supply Unit	15V/2A
Protocols	Ademco Contact ID
Tamper	YES
Mobile Client	Smart Security (IOS/Android)
WEB GUI	YES
CMS	Support 2 CMS Server Address, Main Server + Backup Server (Meian Server/SIA-TCP,-SIA-UDP)
Camera Support	Unlimited for the Quantity
Low Battery Indication	Detector sends the status report to host panel every 1 to 3 hours, the corresponding Zone No. And voltage symbol will be display on the LCD screen and also report to the CMS
Duress Password	The host can make the illusion of disarming when the users is threat-ened by the intruder and actually still send an alarm message to notify the alarm receiver.
Zone Type Programmable	Users can program all preset zone types according to needs. Support delay zone, perimeter zone, internal zone, SOS, 24H, Fire alarm.
WIFI Cameras	Users can access to MEIAN WiFi camer-as at unlimited quantities from App (Smart Security), each cameras can link to one of the wireless and wired zone devices to alarm. Once triggered, users can browse the alarm video and alarm data from the App and alarm center.
Zone Name Programmable	User can learn the device and edit the zone name by manual from App. If devices be triggeres. It will report thr alarm data (Zone No. And Zone Name) indication on the LCD display. Also CMS, SMS and APP.
All Around Safeguard	System with all around safeguard notifications. Door open/closed, devices low battery notification, AC On/Off, Tamper Alarm, Vandal Alarm, Duress Alarm, Fire Smoke and Gas Leakage, Water Leakage, Vibration Detector, Glass Break Alarm, Curtain Intruder Alarm, CCTV and camera monitoring Alarm.