XTEND INDONESIA
GLOBAL LEADING AI TECH COMPANY

www.xtendindonesia.co.id

Burglary Alarm

PSTN Control System

FC-7668 PRO

- 8 tamper-checking wired zone,32 wireless zone.
- 8 programmable access wireless remote.
- 8 programmable access keypad, 32 wireless appliance switch,8 wireless siren.
- Can extend GPRS wireless communication module, support GPRS data transmission.
- Can extend programmable Relay module,serial module.
- Can set 8 private telephone numbers.
- Remote voice prompt operation.

FC-7668 is a intelligent alarm control system which integrated with burglar proof, fireproof, gas leak proof. it is compatible with wired and wireless alarm mode. it use advanced coding techniques of BUS zone and multi-bit random code hopping techniques in security and reliability. to avoid false alarm and interference effectively. adopt SMS, 2G/4G, high-speed Contact ID alarm transmission mode. this system is wirdely used in residence community, villa, shops, offices.

Specification

General	
System NetworkT	TCP/IP+2G/4G Dual NetworkT
Alarm Zones	32 Wireless+8 Wired + 56 RS485 + 32 Power Bus
Dimensions	290x240x87 mm (WXHXD)
Housing Material	ABS Fire-resistant Box
Wireless Frequency	433MHz/868MHz
Installation Location	Indoor Use For Wall Mounted
Menu Voice Guidance	Customized
DHCP Function	Support
Duress Password	Yes
Entry & Exit Delay	Yes
Number of Users	32 Users + 1 Admin +1 Main
Number of voice phone No.	16
Number of wireless remotes	8
Number of wired keypad	16(Each keypad support extra 3 wired zones)
Number of wireless doorbell	1
Number of wireless Switch	32Ch
Partitions And Areas	8
Event log	512
Wireless Siren	4 for dual way siren, multiple for single way siren
PGM Outputst	4
Event log	1000
Backup Battery Type	12V DC, 7ah lead acid battery
Max. run time on backup Battery	16 h if connect 1 wired keypad
Max. receiving range (outdoors)	100 m
Max. sending range (Outdoors)	150 m
Power Supply Unit	15V/3A
GSM Dialing Protocols	Ademco Contact ID
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, Meian CMS
CMS Platform Docking Way	Support 2 CMS Server Address Main Server +Backup Server (Meian Server/SIA-TCP,SIA -UDP)
Camera Supported	Support
WEBIE	Support
Packing	4 Sets/Carton
Certifications	CE,FCC,ROHS