XTEND INDONESIA
GLOBAL LEADING AI TECH COMPANY

www.xtendindonesia.co.id

Curtain PIR

Motion Detector Wired

MD-442DMT

MD-448DMT

DDP-968

Specification

Overview	
Detection	Quad Infrared
Working voltage	9～15VDC
Working current	8mA～25mA
Alarm output	solid relay ,NC output
Tamper interface	N.C，50mA/30VDC
Anti-white light	wireless signal transmitting
Transmitting frequency	>8000LUX
Installation mode	wall-mounted or Ceiling
Installation height	Max.4.8m
Dimension	86×86×50mm

Overview	
Detect angle	200°
Detect distance	6m/25℃
Transmit distancet	150m（open air）
Current consumption	standy <25μA. when transmitting 10mA
Alarm output	wireless signal transmitting
Anti-tamper output	wireless signal transmitting
Transmitting frequency	433MHz
LED indication	Red LED on stands making alarm blue LED on and red led off stands get signal but wrong direction.
Wall mount height	2.5-4m
Woking temperature	-10℃-50℃ (14°F-122°F)

Overview	
Detection	2group quad PIR + dual MW
Detection distance	3m@25℃
Detection angle	20°
MW frequency	10.525GHz
Working voltage	9VDC～15VDC
Working current	100μA(standby) 35mA(alarm)
Installation	height：1.8m～2.4m
Working temperature	-10℃ - +50℃
Anti-white light	>15000LUX
Anti-EMI	>30V/m (30MHz～1GHz)
Emitting frequency	433MHz/868MHz
Emitting power	≤10dB
Dimension	230mm×66m-m×36mm