Door Magnetic

Contact Sensor Wireless

MD-210R

- A. Adopted low consumption CPU
- B. Adopted unique Mutil codes
- C. Auto status report
- D. Anti-lost report
- E. Open door/window indication

The MD-210R is a fully supervised mini style magnetic contact transmitter. It features door/window close/openinstant alarm function. It can be connected to the control panel. It can transmit strong wireless signal, having strong intensity in 150m area. Pleas code it to the control panel before using, enrolling the only one address code to the control panel. When the distance between the magnetic stripe and transmitter beyond 2.5cm the transmitter will send alarm information to the panel. This detector can change wired signal to wireless signal, Working as a transmitter.

Specification

Overview	
Wireless sending distance	inset antenna 150m (open area)
Code	28-digi t ID, 8-digit function code, 36 digits data code in total
Working frequency	433MHz
Working voltage	3V lithium battery
Battery life	about 1 year
Current static	≤5uA
Current alarm	7-12mA (433MHz) ; 35-45mA (868MHz)

Alarm output	alarm, tamper
Status report	after fist electro motion or reset the detector the magnetic switch report the working status to the control panel separately after 30 seconds, 2 minutes,6minutes. And report working status every two hours to the control panel.
Working Temperature	-10℃~50℃
Dimesion	81(L)*32(W)*25(H)mm,
Magnetic stripe	74.5 (L)*13.5(W)*18.8(H)mm
Color	White