XTEND INDONESIA
GLOBAL LEADING AI TECH COMPANY

www.xtendindonesia.co.id

Gas Detector

Wireless LPG Gas Leak Detector

MD-2003R

This product selects the most advanced small current imported gas sensor, can detect the leak gas in a timely manner, the use of professional wireless technology to accurately reflect the alarm situation.Elegant streamlined design, convenient installation, can also be used as part of the home decoration.

- New Nanotechnology sensor
- Automatic reset, it will disconnect automatically, when obviate alarm
- Gas detected: coal gas, natural gas, LPG(liquefied petroleum gas)
- Automatic fault detection
- With solenoid valve drive functions, automatic or manual on / off solenoid valve.

Specification

Overview	
Test gas	natural gas
Power supply	DC 9V-16V
Working current	Monitor: MP-4 ≤75MA
	Alarm: MP-4 ≤300MA
Transmission frequency	433MHz
Speaker volume	≥80dB/m
Alarm concentration	8% LEL

Working environment	-10°C~40°C
Relative humidity	≤ 90% RH
Stability	Long-term work alarm concentration is not greater than ± 5% LEL
Repeatability	Repeat test alarm concentration no more than ± 5% LEL
Alarm concentration error	no more than ± 5% LEL
Alarm mode	sound and light alarm, the output wireless signal, NC / NO output
Power consumption	no more than 5W