XTEND INDONESIA
GLOBAL LEADING AI TECH COMPANY

www.xtendindonesia.co.id

LCD Displ ay

WIFI GPRS Intruder Alarm Security System

ST-IIID

Specification

Overview	
Network	TCP/IP 4G, GPRS
Frequency	433/868MHz (Optional)
App Name	Smart Security
Upgrade Method	Upgrade from IE interface
Surface	Glass surface touch with metal ring, PVC surface
Zones	8 Wires, 32 Wireless, no expander
Event Log	512
Standard Kit	1 x Panel ST-VGT, 1 x PIR MC-335DMT, 1 x Door Sensor MD-210R, 2 x kEY foB PB-403r, 1 X Power Adapter.

Battery	7.4V/200mA Lithium battery (MSDS available), battery life 10 hours
Power Adapter	12V/1.5A EU/US/UK plugs
Accecories (Optional)	All focus wireless accessories include smoke/gas/glass break detector, electric switch and all others.
Voice Prompting	English/French/Italian/Spanish/Turk ish (Optional), Customized language available.
Notification	Phone Call, SMS, App push notifica- tion.
Voice Number	2 CMS number (Aldemco Contact ID), 4 Users voice numbers
IP/GPRS CMS Protocol	SIA-TCP,SIA-UDP,Focus provate IP Protocol