XTEND INDONESIA
GLOBAL LEADING AI TECH COMPANY

www.xtendindonesia.co.id

MINI NVR

MA IV

Specification

General	
P2P	Video Transmit Via P2P Alarm Command Transmit Via CMS
Alarm Zones	64 Wireless Zones + 2 Wired Zones
Network	IP+2G/4G
Video Input	4*1080P IP Camera
Video Output	1 HDMI Output 1 VGA Output
Video Compression	H.265
Playback	3CH 1080P
Motion Detection	396(22×18)detection areas, Sensibility 6 levels adjustable
Blocked Area	Can be set 4 Blocked Areas
Audio Coding Standard	G711A, Rate, 8khz, 16bit
Audio Input	Support front-end ipc audio input
Audio Output	Built in speaker
Voice Intercom	1 CH dual way communication
GSM SMS	Arm/disarm,Status Query, Light Swtich, PGM Control
E-mail	YES
IE Remote Control	YES
Alarm Receiving Phone	2 CMS, 4 Voice phone, 2 Free Arm /Disarm Phone No.
Alarm Center Protocol	SIA-2013,Meian Protocol,Contact ID
Partition Control	4 Partitions
Arm/Disarm Timing	4 Groups
Tamper Alarm	YES
Internet Protocol	Static IP,DHCP
Ethernet Port	1 RJ45 10M/100M auto adapative
GPRS/4G	1 UIM, Support GPRS/4G for optional
USB Port	2.0 USB, 1.0 USB

Keypad Support	8
Remote Support	8
Switch Support	64PCS
Wireless Frequency	433Mhz/868Mhz
HDD Port	SD Card 128G
Battery (Excluded)	3.7V/1000MAH
Power Supply	DC12V/3A
Product Size	150 x 150 x 30mm
Smartphone APP	IOS/Andriod