PIR Detector

Wired PIR Motion Detector

MC-215

MC-800DMT

Passive infrared intrusion detector for detecting accidental or malicious intrusion, to meet a demand for your protection. The design for the small size round white stained flow line shape, can be installed on the wall or a 45 ° angle with the wall installation, ideal installation height is 1.8m-2.4m from the ground under the protection zone can be avoided, as the protective corners, you can set the sensitivity to accommodate the installation environment. This product has a built-in tamper switch to prevent unauthorized removal.

Specification

Overview	
Detection	Quad Infrared+Artificial Intelligence
Working voltage	9~16VDC
Current consumption	About 15mA@12VDC
Alarm output	N.C, 100mA/30VDC
Tamper interface	N.C, 50mA/30VDC
Anti-white light	>9000LUX
Installation mode	Wall-mounted
Installation height	1.8m-2.4m
Dimension	87 * 61 * 41 mm

Overview	
Detection	Quad Infrared
Working voltage	9~16VDC
Working current	8mA~25mA
Alarm output	N.C, 50mA/30VDC
Tamper interface	N.C, 50mA/30VDC
Anti-white light	>9000LUX
Installation mode	Wall-mounted
Installation height	1.8m-2.4m
Dimension	92 * 61 * 44 mm