


Smart PoE IVR

IA-4-64-D

4HDD 64CH
4K H.265+



H.265+ 64CH IVR, support 64CH 4K IP camera input and output, support smart analysis IPC, 1 CH 4K/4CH 1080P/16 CH sub-code stream playback, 4 pcs HDD (max 10TB), 1CH VGA, 1 CH HDMI, support to upgrade IPC remote, modify IP camera address and light board mode, support alarm and audio, support RAID function.

Highlight

- Support H.265+/H.265/H.264 dual stream decoding, 64CH 4K IP camera input
- Support synchronous recording, remote monitoring, backup; up to 16CH 1080P video synchronous playback and multi-channel backwards playback
- Support to upgrade IPC online and upgrade IPC through memory
- Support to modify my company IP address and light board mode
- Support to add IPC manually or automatically in LAN
- Support 30min instant playback, 30s pre-record
- Standard ONVIF, SLINK, RTSP protocol
- Support DDNS, EMAIL, UPNP, NTP, P2P and other functions
- Support WEB, mobile phone monitoring, client, IMS monitoring
- Support external alarm; Two-way audio intercom
- Support our Smart IPC: target count, electric fence, human detection, retrograde detection, absent alarm
- Support IPC centralized management, including IPC parameter configuration, information export and import, real-time information acquisition and upgrade, etc
- Support channel grouping, preview tour
- Supports disk grouping quotas and disk group storage modes,support RAID0, RAID1, RAID5, RAID6, RAID10... matrix style
- Support network HDD (IPSAN,NAS), double password authentication
- Support network monitoring: network traffic, network delay packet loss test, network packet capture backup
- Support multiple language, micro-intelligence, capture playback

Specification

Storage		Video & Audio	
HDD	4 SATA, max 10TB HDD	Video Output	1 HDMI, 1 VGA
E-Sata	N/A	Audio Input & Output	1 RCA in, 1 RCA out, HDMI audio
		Alarm Input & Output	4 in 4 out
Network		External Ports	
Network Interface	2*RJ45 10M/100M/1000M self-adaptive LAN port	USB	3 USB ports (2 USB2.0, 1USB3.0)
Network Function	DDNS, EMAIL, UPNP, NTP, DHCP, IP Filter, PPPoE, P2P	RS232	N/A
Smart Phone	iPhone, android	RS485	1

System	
Main Chipset	Hi3536
Operating System	Embedded Linux
Bandwidth	512M
Video Format	H.265+/H.265/H.264
Video Resolution	4K/5MP/3MP/1080P/720P/D1
Smart Functions	Target count, electric fence, human detection, retrograde detection, absent alarm (need front end IPC supported)
Record Mode	Manual, Schedule, Motion Detection, Timing, Alarm, Stop
Playback	1CH 4K/4 CH 4K/9*3Mp/ 16CH 1080P
Backup Mode	USB Device/Network
Display mode	36ch Digital (4000X3000) + 36ch Preview + 16ch Playback 64ch Digital (4000X3000) + 64ch Preview + 16ch Playback

Human Detection									
Normal Mode					36 CH normal IPC				
Split	1	4	6	8	9	16	25	36	
Decode	4K	4K	4K + 5*2mp	4K + 7*2mp	2MP	1080P	720P	D1	
Normal Mode					64 CH normal IPC				
Split	1	4	6	8	9	16	25	36	64
Decode	4K	4K	4K + 5*2mp	4K + 7*2mp	2MP	1080P	720P	D1	D1

Others	
Power Supply	DC12V 6.25A
Power Consumption	≤25W (without HDD)
Dimension	Equipment: 440mm × 355mm × 70mm Packing: 560mm X 440mm X 135mm
Weight	5.5kg (without HDD) with package 6kg
Outside Carton	2pcs/Carton; Dimension: 570mm × 290mm × 490mm, 12.5kg

Size

