Smart Socket
Wireless

smart socket is easy to control and with socket conversion as a whole. with intelligent remote control functions. it is a smart and secure products. smart socket can be plugged directly into other sockets or plug into the power strip. there are two USB ports and power socket accessible. smart socket for any types of socket to be converted places, such as hotel, office, home. etc.

PL-300R

PL-508

HA-4502

Specification

Overview	
Working voltage	DC 12V
Working current	<200Ma@max
Relay output power	0A/14VDC 10A/125VAC
Debug Mode	ASK/FSK for options
Working Frequency	433mhz
Wireless distance	(L*W*H) 70*70*25mm
Installation	wall inside, wall mounting

Overview	
WorkInput Voltage	100v-240vAC
Working frequency	50~60Hz
Radio frequency	433MHz
RF Transmitting distance	100 meter indoor
Voltage Range	110Vac-230Vac/50HZ-60HZ
Operate Temperature	-10°C ~ 55°C
Socket output power	3kw

Overview	
Input voltageT	125V
Input frequency	50Hz/60Hz
Max.load current	10A
Max.Power	2200W
WIFI standard	WIFI 802.11 b/g/n
WIFI frequency	2.4GHz
Receive Sensitivity	98dBm
PA output	19.5dBm
Total consumption	TBD
Indicator light	Blue LED
Reference	FCC/CE/RHOS